

Subject to priorities defined by the Steering Committee and the Presidium, the results of *fib*'s work in Commissions and Task Groups are published in a continuously numbered series of technical publications called 'Bulletins'. The following categories are used:

category	minimum approval procedure required prior to publication
Technical Report	approved by a Task Group and the Chairpersons of the Commission
State-of-Art Report	approved by a Commission
Manual or Guide (to good practice)	approved by the Steering Committee of <i>fib</i> or its Publication Board
Recommendation	approved by the Council of <i>fib</i>
Model Code	approved by the General Assembly of <i>fib</i>

Any publication not having met the above requirements will be clearly identified as preliminary draft.
This Bulletin N° 34 will be submitted to the General Assembly for approval as an *fib* Model Code in June 2006.

This report was prepared within Task Group 5.6, *Model code for service life design of concrete structures*:

Peter Schiessl (Convener, Technische Universität, München, Germany)

Phil Bamforth (Principal Construction Consultancy, UK), Véronique Baroghel-Bouny (LCPC, France), Gene Corley (Construction Technology Laboratories, Inc., USA), Michael Faber (ETH-Zürich, Switzerland), Jim Forbes (Hyder Consulting, Australia), Christoph Gehlen (Ingenieurbüro Schiessl, Germany), Paulo Helene (Univ. de Sao Paulo PCC/USP, Brazil), Steinar Helland (Skanska Norge AS, Norway), Tetsuya Ishida (Univ. of Tokyo, Japan), Gro Markeset (Norwegian Building Research Institute, Norway), Lars-Olof Nilsson (Lund Institute of Technology, Sweden), Steen Rostam (Cowî A/S, Denmark), A.J.M. Siemes (TNO, The Netherlands), Joost Walraven (Delft Univ. of Technology, The Netherlands)

Full address details of Task Group members may be found in the *fib* Directory or through the online services on *fib*'s website, www.fib-international.org.

Cover images: The photos show the carbonation depth of a vertical concrete surface of an existing building after 8 years of exposure without shelter from rain. A phenolphthalein indicator distinguishes areas with $\text{pH} < 9.5$ (not coloured) and areas with a higher pH (coloured). The graph shows the development of the carbonation depth over time, $x_c(t)$, compared to the cover depth, a . Scatter of both variables is also given.

© fédération internationale du béton (*fib*), 2006

Although the International Federation for Structural Concrete *fib* - fédération internationale du béton - created from CEB and FIP, does its best to ensure that any information given is accurate, no liability or responsibility of any kind (including liability for negligence) is accepted in this respect by the organisation, its members, servants or agents.

All rights reserved. No part of this publication may be reproduced, modified, translated, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission.

First published in 2006 by the International Federation for Structural Concrete (*fib*)

Post address: Case Postale 88, CH-1015 Lausanne, Switzerland

Street address: Federal Institute of Technology Lausanne - EPFL, Section Génie Civil

Tel +41 21 693 2747, Fax +41 21 693 6245, E-mail fib@epfl.ch, web www.fib-international.org

ISSN 1562-3610

ISBN 2-88394-074-6

Printed by Sprint-Digital-Druck, Stuttgart